



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

ATF 95 LE (TYPE M)

FOR USE IN FORD 4 SPEED AUTOMATIC TRANSMISSIONS

DESCRIPTION

ATF Type 95LE is an approved service fill for the Ford 4 speed electronically controlled automatic transmissions made by BTR (these are models LE 85, LE 91, LE 95 and LE 97). These automatic transmissions have been fitted to various 6 and 8 cylinder Ford Falcon, Fairmont, Fairlane and LTD models since 1989. ATF Type 95LE can also be used in transmissions that call for a Type M type fluid.

Note: Although ATF 95LE has specifications satisfying the requirements of Dexron® II, it is not a Dexron® II qualified product. It was formulated for BTR transmission and type M hence should only be used in such applications.

SUMMARY OF BENEFITS

- Fully approved by BTR for Service Fill
- Very good gear durability from specialised additives
- Highly stable fluid ideally suited to long distance towing in hot weather
- Smooth gear changes due to optimal frictional characteristics
- Low noise
- Also suitable for use in Mitsubishi transmissions that call for a Type M automatic fluid

SPECIFICATIONS

ATF Type 95LE meets the following international performance specifications:

- Approved by BTR Engineering for service fill in the following Ford 4 speed Automatic Transmissions:
 - 85 LE, 91 LE, 95 LE and 97 LE
 - Allison C-4, TES-389
 - Volvo 97340
 - VOITH H55.6335.XX
 - ZF TEMPL05L, 09, 21L
 - Caterpillar TO-2
 - GM IIIH, IID, IIE

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

ATF 95 LE (TYPE M)

FOR USE IN FORD 4 SPEED AUTOMATIC TRANSMISSIONS

TYPICAL CHARACTERISTICS

ATF 95 LE (TYPE M)	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8731
Kinematic Viscosity @ 40°C	ASTM D445	cSt	40
@ 100°C	ASTM D445	cSt	7
Viscosity Index	ASTM D2270	-	143
Brookfield Viscosity @ -40°C	ASTM D2983	cP	34,000
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D92	°C	148
Copper Corrosion 3Hr/100°C	ASTM D130	-	1A
Appearance			Red

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 30042, 60lt - 36042, 20lt - 32042, 5lt - 30442 and 1lt - 30142

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398