



GULF WESTERN

THE TOUGH AUSTRALIAN

PRODUCT DATA

Gulf 1 10W-60 SN

Fully Synthetic Premium Petrol / Light Diesel Engine Oil

Description

Gulf 1 is a fully synthetic premium petrol engine / light diesel oil designed for car enthusiast looking for ultimate engine protection. It is formulated with polyalphaolefin (PAO) which is the highest performing synthetic base oil. It meets the latest specifications of all modern engine manufacturers and OEM's.

It provides exciting performance characteristics and all season protection, controlling low temperature sludge and high temperature oxidation. It is recommended for:

- Street Machines / Racing and high performance race cars.
- All diesel engined light commercials and cars.
- LPG or CNG fueled vehicles.
- Cars running multi valve engines.

Summary of Benefits

Gulf 1 offers:

- Extended drain intervals for more up time.
- Fully synthetic providing fuel saving capability.
- Fully synthetic providing reduced oxidation and viscosity breakdown.
- Superior sludge and varnish control for a cleaner engine.
- Reduced oil consumption due to improved volatility control.
- Greatly reduced engine wear giving extended engine life.
- Very good low temperature viscometrics for reduced wear at start up.

Specifications

Gulf 1 meets the following international performance specifications:

- SAE Viscosity 10W-60
- API SN
- ACEA A2-96, B2-96
- Ford ESE- M2C -153E

Gulf 1 10W-60 SN

Fully Synthetic Premium Petrol / light diesel Engine Oil

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Gulf 1	10W-60	
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.8584
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	130
@ 100°C	ASTM D445	cSt	>21.9
Viscosity Index	ASTM D2270	-	170 min
Pour Point	ASTM D97	°C	-30
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	7
Sulphated Ash	ASTM D874	% mass	<1.15

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

205lt - 30034, 20lt - 32034, 5lt - 30534



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398