



GULF WESTERN

THE TOUGH AUSTRALIAN

PRODUCT DATA

Hi Tech Premium 20W-50

Wide Range Multi Grade Engine Oil

Description

Hi Tech Premium is a premium wide range motor oil designed for modern and older engines making it an excellent mixed fleet oil. It is formulated with state of the art lubrication technology. It meets the latest specifications of nearly all modern engine manufacturers and OEM's.

It provides all season protection, controlling low temperature sludge and high temperature oxidation. Recommended for:

- Cars running on Leaded and Unleaded Petrol • LPG or CNG fueled vehicles
- Cars running multi valve engines
- Light diesel engines

Summary of Benefits

Hi Tech Premium offers:

- Extended drain intervals for more up time.
- Satisfies the performance requirements. of Japanese, European and American car manufacturers.
- Superior sludge and varnish control for a cleaner engine.
- Greatly reduced engine wear giving extended engine life.
- Very good low temperature viscometrics for reduced wear at start up.

Specifications

Hi Tech Premium meets the following international performance specifications:

- SAE Viscosity 20W-50
- API SN/CF
- ACEA A2-96, B2-96
- Ford ESE- M2C -153E
- Passes the performance requirements of Japanese VTW
- MIL-L-46152E, 2104E

Hi Tech Premium 20W-50

Wide Range Multi Grade Engine Oil

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Hi Tech Premium	20W-50	
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.892
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	145
@ 100°C	ASTM D445	cSt	18.6
Viscosity Index	ASTM D2270	-	125
Pour Point	ASTM D97	°C	-24
Flash Point (COC)	ASTM D92	°C	200
Total Base Number	ASTM D2896	mgKOH/g	6.6
Sulphated Ash	ASTM D874	% mass	1.15

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

IBC - 30027B, 205lt - 30027, 20lt - 32027, 6lt - 30627, 5lt - 30527, 1lt - 30127



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398