



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

MINERAL COMPRESSOR SERIES

MULTI PURPOSE MINERAL COMPRESSOR OIL

DESCRIPTION

The Compressor Series is a premium quality mineral, multi purpose range of compressor oils. Formulated for use in rotary vane, reciprocating, axial and screw air compressors.

Note: Not suitable for use in compressors producing air for breathing. It is available in ISO Viscosity Grades 46, 68 and 100.

SUMMARY OF BENEFITS

- Formulated with state of the art additive packages incorporating the latest technology
- Provides state of the art anti wear additives for longer component life
- Provides good filterability and demulsibility important in rotary screw compressors, where separators are expensive
- Provides good hydrolytic stability for protection from entrained moisture

SPECIFICATIONS

Mineral Compressor meets the requirements of most modern manufacturers of air compressors, including but not limited to:

- Atlas Copco -Model GA & GAU series
- Jaeger Machine Company rotary screw & vane
- Atlas Copco portable rotary screw XA XAH
- LeRoi Division
- Dresser Industries both portable & stationary (including no aluminum vanes)
- Meets DIN 51506 (VBL, VCL, VDL), ISO DP6521, (DAH/G)

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

MINERAL COMPRESSOR SERIES

MULTI PURPOSE MINERAL COMPRESSOR OIL

TYPICAL CHARACTERISTICS

COMPRESSOR	Test Method	Units	46	68	100
Density @ 15°C	ASTM D1298	kg/L	0.859	0.863	0.870
Kinematic Viscosity					
@ 40°C	ASTM D445	cSt	46	68	100
@ 100°C	ASTM D445	cSt	6.9	9	11
Viscosity Index	ASTM D2270	-	96	96	96
Pour Point	ASTM D97	°C	-27	-27	-18
Flash Point (COC)	ASTM D92	°C	212	218	242

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

46: IBC - 30085B, 205lt - 30085, 20lt - 32085

68: IBC - 30075B, 205lt - 30075, 20lt - 32075, 1lt - 30175

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398