



GULF WESTERN
THE TOUGH AUSTRALIAN

PRODUCT DATA

Protecta Ultra 15W-50

Semi Synthetic Premium Petrol Engine Oil

Description

Protecta Ultra provides semi synthetic protection in extreme and normal operating conditions. It suits all petrol and small diesel engines and is designed for the modern multi valve engine, turbocharged and high performance applications. It is formulated with synthetic base stock for superior performance. It meets the latest specifications of nearly all modern engine manufacturers and OEMs.

It provides high performance wear control, wide temperature range fluidity, minimisation of low temperature sludge and high temperature oxidation varnish formation. Recommended for:

- Cars running on Leaded and Unleaded Petrol.
- All diesel engined light commercials and cars.
- LPG or CNG fueled vehicles.
- Cars running multi valve engines or turbochargers.

Summary of Benefits

Protecta Ultra offers:

- Extended drain intervals for more up time.
- Semi synthetic providing fuel saving capability.
- Semi synthetic providing reduced oxidation and viscosity breakdown.
- Superior sludge and varnish control for a cleaner engine.
- Superior circulation performance.
- Reduced oil consumption due to improved volatility control.
- Greatly reduced engine wear giving extended engine life.
- Very good low temperature viscometrics for reduced wear at start up.

Specifications

Protecta Ultra meets the following international performance specifications:

- SAE Viscosity 15W-50
- API SH, SJ, SL, CF4
- ACEA A2-96, B2-96
- Ford ESE- M2C -153E
Passes the performance requirements of Japanese VTW
- MIL-L-46152E, 2104E

Protecta Ultra 15W-50

Semi Synthetic Premium Petrol Engine Oil

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Protecta Ultra	15W-50	
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.889
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	120
@ 100°C	ASTM D445	cSt	18
Viscosity Index	ASTM D2270	-	140
Viscosity at 15°C	IP 383	cP	3200
Pour Point	ASTM D97	°C	-30
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	8.5
Sulphated Ash	ASTM D874	% mass	1.15

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available: 205lt - 30033, 20lt - 32033, 5lt - 30533



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398