



GULF WESTERN
THE TOUGH AUSTRALIAN

PRODUCT DATA

Synfleet MX 10W-40

Full Synthetic Ultra Premium Diesel Engine Oil

Description

Synfleet MX is a synthetic ultra premium diesel engine oil meeting the latest in lubrication technology. Synfleet MX utilises the latest specification in diesel additive technology. Synfleet MX is specifically formulated for use in the latest emission engines operating under the most severe conditions including multi trailer and high horsepower applications. Synfleet MX has been developed to satisfy the increasing demands for extended service intervals when supported by routine oil analysis. The inherent high temperature stability of Synfleet MX enables this oil to provide a level of protection not normally available in non PAO based diesel engine oils.

Summary of Benefits

Synfleet MX offers:

- Extended drain intervals for increased up time.
- Superior thermal stability and component protection under severe operating conditions.
- Reduced oil consumption.
- Greatly reduced friction and engine wear giving extended engine life.
- Superior sludge and soot control for a cleaner engine.
- Outstanding low temperature viscometrics for reduced wear at start up.

Specifications

Synfleet meets the following international performance specifications:

- SAE Viscosity 10W-40
- API CJ4/SN
- ACEA E7
- Global DDH-1
- Cummins CES 20081
- Mack EO-O Premium Plus
- Mercedes-Benz sheet 228.3
- Volvo VDS-4
- Allison C4
- Caterpillar ECF3, ECF 1, and T0-2
- MTU Type II
- DDC 93K218
- MAN 3275

Synfleet MX 10W-40

Full Synthetic Ultra Premium Diesel Engine Oil

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Synfleet MX 10W-40		
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.891
Kinematic Viscosity			
@ 40°C			101
@ 100°C	ASTM D445	cSt	15.5
Viscosity Index	ASTM D2270	-	163
Pour Point	ASTM D97	°C	-34
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	7.7
Sulphated Ash	ASTM D874	% mass	<1.00

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

IBC - 30014B, 205lt - 30014, 20lt - 32014



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398