



GULF WESTERN
THE TOUGH AUSTRALIAN

PRODUCT DATA

TRANSYN-MF ATF

High Quality multi functional ATF

Description

Transyn-MF is a synthetic blend multi functional Automatic Transmission Fluid. It meets the requirements of a wide range of American, Japanese and European OEM's.

Transyn-MF is a mid-tier ATF and is does not meet some of the OEM requirements of SYN-TS, most notably 6 Speed ZF transmissions that require a fluid meeting ZF-TE-ML-09.

Summary of Benefits

- Synthetic blend
- Suitable for extended drain intervals where standard Dexron III mineral oils are required.
- Reduces the need to stock additional fluids.
- Friction modified formulation.
- High VI, Shear stable blend that offers excellent cold start flow properties.
- Ideal for heavy duty applications such as towing and long distance driving in very hot or cold climates
- Can be used where a Dexron IID, III, IIIE, VI, Ford 95le, ATF+4, SPIII and C4 fluids are called for.

TRANSYN-MF ATF

High Quality multi functional ATF

Specifications

Transyn-MF ATF is suitable for use where the following specification is called for (please note this is a summary, for more details please contact Gulf Western Technical):

- Dexron III
- ATF+3,+4
- ATF JWS 3309
- Alison TES295, 389
- Chrysler AS68RC, SP-III
- Mercedes Benz 236.1, 236.11, 236.12, 236.14, 236.15, 236.3, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9 & 236.91
- Ford WSS-M2C922-A1
- TYPE A Suffix
- Honda DW-1, Z-1
- Hyundai / Kia Genuine, 1K, JWS 3309, NWS 9638 T-5
- Isuzu Genuine ATF
- Jaguar Fluid 8432, JLM 20238, 20292, 21044, K17
- Land Rover TYK500050
- MAN 339A
- Maserati 231603
- Mazda F1, FZ, JWS3317, M5, MIII, T-IV
- Mitsubishi J2, J3, SPII/III
- Nissan Matic D, J, K, S, W
- Porsche 043 204 41, 205 09, 205 28, 304 00, 999 917 547 00(A2)
- Renault Matic D2
- SAAB 3309 T-IV, 93 165 147 – AW1
- Subaru HP
- Suzuki 3314, 3317
- Toyota / Lexus DII, T, T-III, T IV
- VW / Audi 052 – 025A2, 055, 162, 533, 990, 055 005, 025, 540, 000 162
- Volvo PN 1161521, 1161540 / 1161640
- ZF TE-ML 11A, TE-ML-11B

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

TRANSYN-MF ATF

High Quality multi functional ATF

Typical Characteristics

Grade:	TRANSYN-MF ATF		
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.855
Kinematic Viscosity			
@ 40°C	ASTM D445		31
@ 100°C	ASTM D445	cSt	6.4
Viscosity Index	ASTM D2270	-	165
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D92	°C	224

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

205lt - 60058, 60lt - 66058, 20lt - 62058



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398

