



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

SYN-X 5000 5W-40

FULL SYNTHETIC, SN/CF, A3/B4-16, MB 229.5, VW 502.00, 505 00, RENAULT RN0700

DESCRIPTION

Syn-X 5000 5W-40 is a full synthetic specially engineered high performance engine lubricant suitable for many late model passenger vehicles, 4WD/SUV and Light Commercial vehicles operating on either Petrol, LPG or Diesel fuels. Not suitable for vehicles with DPF.

Formulated to exceed the requirements of API SN/CF, ACEA A3/B4 and the stringent MB 229.5 requirements, Syn-X 5000 5W-40 is suited to high performance engine applications including turbo and supercharged engines.

Exceptional deposit and sludge control, resistance to oxidation and nitration and high levels of wear protection ensure engine cleanliness, enhanced oil durability and cost savings with regular use.

SUMMARY OF BENEFITS

- Full Synthetic formulation offering enhanced temperature-viscosity characteristics and higher resistance to breakdowns
- Super oxidation stability enabling longer oil drain intervals
- Excellent soot and sludge control resulting in cleaner engines
- Excellent stop-start wear protection
- Excellent mixed fleet oil, suitable for European, American and Asian petrol and diesel engines

SPECIFICATIONS

Syn-X 5000 5W-40 meets the following international performance specifications:

- API SN/CF
- ACEA A3/B4
- Mercedes Benz 229.5
- Volkswagen 502.00/505.00
- Renault RN 0700
- JASO MA

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

SYN-X 5000 5W-40

FULL SYNTHETIC, SN/CF, A3/B4-16, MB 229.5, VW 502.00, 505 00, RENAULT RN0700

TYPICAL CHARACTERISTICS

SYN-X 5000 5W-40	Test Method	Units	Results
Density @ 15°C	ASTM D7042	kg/L	0.855
Kinematic Viscosity @ 40°C	ASTM D7042	cSt	89.6
@ 100°C	ASTM D7042	cSt	14.6
Viscosity Index	ASTM D7042	-	169
Apparent Viscosity @ -30°C	ASTM D5293	cP	6250
Pour Point	ASTM D97	°C	-39
Total Base Number	ASTM D2896	mgKOH/g	10.8
Sulphated Ash	ASTM D874	%	1.20

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 60037, 20lt - 62037, 5lt - 60537, 1lt - 60137

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398