



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

SYN-X 5000 10W-40

FULL SYNTHETIC, SN/CF, ACEA A3/B3-12, A3/B4-12, VW 502 00, 505 00, MB 229.3

DESCRIPTION

Syn-X 5000 10W-40 is a full synthetic specially engineered high performance passenger car lubricant suitable for late model passenger motor vehicles. Formulated to meet API SN/CF and ACEA A3/B4-12 requirements, Syn-X 5000 10W-40 is ideally designed for many Australian, European, Asian and American manufactured vehicles calling for these oil specifications making it an excellent mixed fleet oil.

Syn-X 5000 10W-40 also meets major European OEM requirements such as those from Volkswagen, Mercedes Benz, Renault and more.

SUMMARY OF BENEFITS

- Full Synthetic formulation offering enhanced temperature-viscosity characteristics compared to mineral oil
- Super oxidation stability compared to a mineral oil based lubricant
- Excellent soot and sludge control resulting in cleaner engines
- Reduces fuel consumption due to superior technology
- Outstanding low temperature viscometrics for reduced wear at start up
- Excellent mixed fleet oil
- Suitable for European, American and Japanese diesel engines

SPECIFICATIONS

Syn-X 5000 10W-40 meets the following international performance specifications:

- API SN/CF
- ACEA A3 (2012)
- ACEA B3 (2012)
- ACEA B4 (2012)
- MB 229.3
- RN 700/710
- Volkswagen VW502 00
- Volkswagen VW505 00
- PSA B71-2300

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

SYN-X 5000 10W-40

FULL SYNTHETIC, SN/CF, ACEA A3/B3-12, A3/B4-12, VW 502 00, 505 00, MB 229.3

TYPICAL CHARACTERISTICS

SYN-X 5000 10W-40	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.86
Kinematic Viscosity @ 40°C	ASTM D445	cSt	104
@ 100°C	ASTM D445	cSt	15.4
Viscosity Index	ASTM D2270	-	>150
Pour Point	ASTM D97	°C	-33
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	10.4
Sulfated Ash	ASTM D874	% mass	1.3

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 60037, 20lt - 62037, 5lt - 60537, 1lt - 60137

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398