



GULF WESTERN OIL

THE TOUGH AUSTRALIAN

INDUSTRIAL/OFF HIGHWAY

TECHNICAL DATA SHEET

GEAR LUBE LS 90

SUMMARY OF BENEFITS

- Gulf Western Gear Lube LS 90 fills a dual role as both a limited slip and conventional oil, to rationalise grades
- High level of performance ensures very good wear protection
- Controlled friction modifiers provide quiet, anti-chatter operation of limited slip differentials

SPECIFICATIONS

- SAE Viscosity 90 • API Exceeds GL5 (was GL6 when this was a recognised performance level) • Mack GO-J
- US Military MIL-L-2105D • Meritor 076A

TYPICAL PROPERTIES

CHARACTERISTICS	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	Kg/L	0.8997
Kinematic Viscosity @ 40°C @ 100°C	ASTM D445	cSt	200
	ASTM D445	cSt	18
Viscosity Index	ASTM D2270	-	99
Pour Point	ASTM D97	°C	-12
Flash Point (COC)	ASTM D92	°C	216
Timken Ok Value	ASTM D2782	Kg	27
Four Ball Test	IP 239		
	Weld Load (10 seconds)	Kg	430
	Wear Scar (20Kg 100 Min)	mm	0.3

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

AVAILABLE PACK SIZES

IBC - 30053B, 205lt - 30053, 60lt - 36053, 20lt - 32053 and 1lt - 30153

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.