



GULF WESTERN OIL

THE TOUGH AUSTRALIAN

INDUSTRIAL/OFF HIGHWAY

TECHNICAL DATA SHEET

TOP GAS 600

SUMMARY OF BENEFITS

- Exceptional Oxidation and Nitration resistance
- Low Zinc
- High level of protection
- Exceptional detergent/dispersant properties
- Extensive field service
- Cleaner engines
- Longer oil and filter and service life
- Suitable where corrosive fuels are used
- Excellent valve train protection
- Reduced level of combustion chamber ash

SPECIFICATIONS

- SAE Viscosity 40 • WAUKESHA 7044/7042. Top Gas 600 SAE 40 is suitable for use in a wide range of engines including:
- Caterpillar 3500, 3600 & C280 (self certified) • Jenbacher • Waukesha • API CF

TYPICAL PROPERTIES

CHARACTERISTICS	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	Kg/L	0.8871
Kinematic Viscosity @ 40°C @ 100°C	ASTM D445	cSt	124
	ASTM D445	cSt	13.5
Viscosity Index	ASTM D2270	-	104
Pour Point	ASTM D97	°C	-9
Flash Point (COC)	ASTM D92	°C	224
Total Base Number	ASTM D2896	mgKOH/g	4.2
Sulphated Ash	ASTM D874	% mass	0.5%

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

AVAILABLE PACK SIZES

IBC - 60026B, 205lt - 60026, 20lt - 62026

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.



Oronite

November 2017