



# GULF WESTERN OIL

## THE TOUGH AUSTRALIAN

### INDUSTRIAL/OFF HIGHWAY

## TECHNICAL DATA SHEET

# TORQUE OIL 30 & 50

### SUMMARY OF BENEFITS

- Outstanding frictional characteristics for optimum clutch life
- Excellent compatibility with both seals and frictional material
- Has the ability to control brake chatter, thus extending the life of wet brakes
- Enhanced wear protection leading to longer life

### SPECIFICATIONS

- SAE Viscosity 30 & 50
- API CF GL-4
- Caterpillar T0-4
- Meets the requirements of ZF TE-ML 03C, 07D and 07F
- Torque Oil 30 meets the requirements of Allison C4/TES 439 and Komatsu
- Torque Oil 50 is also suitable for Road Ranger Transmissions

### TYPICAL PROPERTIES

CHARACTERISTICS	TEST METHOD	UNITS	RESULTS - 30W	RESULTS - 50W
Density @ 15°C	ASTM D1298	Kg/L	0.8921	0.9018
Kinematic Viscosity @ 40°C @100°C	ASTM D445	cSt	80	225
	ASTM D445	cSt	10.5	20
Viscosity Index	ASTM D2270	-	105	100
Pour Point	ASTM D97	°C	-27	-18
Flash Point (COC)	ASTM D92	°C	224	230

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

### STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### AVAILABLE PACK SIZES

30W: IBC - 30045B, 205lt - 30045, 20lt - 32045

50W: IBC - 30046B, 205lt - 30046, 20lt - 32046

### HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.