



# GULF WESTERN OIL

## THE TOUGH AUSTRALIAN

### INDUSTRIAL/OFF HIGHWAY

## TECHNICAL DATA SHEET

# ULTRA CLEAR GEAR OIL

### SUMMARY OF BENEFITS

- Gulf Western Ultra Clear Diff Lube synthetic formulation is more resistant to oil oxidation, giving longer drain intervals
- Excellent resistance heat degradation allows this grade to operate at higher temperatures than a mineral gear oil
- Naturally high viscosity index, reduces wear at start up yet still provides better protection at operating temperature
- Reduces friction hence lowering operating temperature and frictional power losses

### SPECIFICATIONS

- SAE Viscosity 80W-140 • MIL -L-2105D • API GL-4 and GL-5 • Mack GO-J

### TYPICAL PROPERTIES

CHARACTERISTICS	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	Kg/L	0.867
Kinematic Viscosity @ 40°C @ 100°C	ASTM D445	cSt	300
	ASTM D445	cSt	30.0
Viscosity Index	ASTM D2270	-	155
Pour Point	ASTM D97	°C	<-30
Flash Point (COC)	ASTM D92	°C	235
Colour	ASTM D1500	-	1.5

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

### STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### AVAILABLE PACK SIZES

IBC - 30055B, 205lt - 30055, 20lt - 32055, 4lt - 30455

### HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.