



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

C4 HYDRAULIC 10W

HYDRAULIC OIL FOR MOBILE PLANT HYDRAULIC EQUIPMENT

DESCRIPTION

C4 Hydraulic 10W is specially designed for mobile plant hydraulic equipment where an SAE 10W oil is specified.

SUMMARY OF BENEFITS

- Excellent oxidation stability ensuring long life
- Very good corrosion and wear protection provides long component life
- Excellent air release and anti-foam properties
- High resistance to thickening in service
- Extremely shear stable, offering constant viscosity for the drain interval

SPECIFICATIONS

C4 Hydraulic 10W meets the following international performance specifications:

- SAE Viscosity 10W
- API CD, SF
- MIL-L-2104D & E
- Allison C4
- Caterpillar T0-2

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

C4 HYDRAULIC 10W

HYDRAULIC OIL FOR MOBILE PLANT HYDRAULIC EQUIPMENT

TYPICAL CHARACTERISTICS

C4 HYDRAULIC 10W	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8723
Kinematic Viscosity @ 40°C	ASTM D445	cSt	70
@ 100°C	ASTM D445	cSt	10
Viscosity Index	ASTM D2270	-	140
Pour Point	ASTM D97	°C	-33
Flash Point (COC)	ASTM D92	°C	>200
Total Base Number	ASTM D2896	mgKOH/g	5
Sulphated Ash	ASTM D874	% mass	<1

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30060B, 205lt - 30060 and 20lt - 32060

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398