

# MONOIL 30

## MONO GRADE DIESEL ENGINE OIL

### DESCRIPTION

Monoil is a high quality monograde diesel engine oil for naturally aspirated and lightly turbocharged diesel engines. It is cost efficient engine oil for diesel engines requiring API CD/SF performance or lower.

This product meets the "series 3" Diesel specification. Monoil is available in SAE grades 30 and 40.

### SUMMARY OF BENEFITS

- Monoil is a cost efficient oil for older engines or those requiring API CD/SF or lower performance
- May be used in those transmission applications requiring Caterpillar TO-2 or Allison C3 performance

### SPECIFICATIONS

Monoil 30 meets the following international performance specifications:

- SAE Viscosity 30
- API CD, SF
- MIL-L-2104D & E
- Allison C3
- Caterpillar T0-2

Monoil 30 meets the minimum warranty requirements of most Japanese diesel engines. It also meets the requirements of many older engines such as Leyland, International Harvester, Gardner, Fiat and Bedford.

### STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

# MONOIL 30

MONO GRADE DIESEL ENGINE OIL

## TYPICAL CHARACTERISTICS

MONOIL 30	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.883
Kinematic Viscosity @ 40°C	ASTM D445	cSt	95
@ 100°C	ASTM D445	cSt	11.4
Viscosity Index	ASTM D2270	-	107
Pour Point	ASTM D97	°C	-18
Flash Point (COC)	ASTM D92	°C	224
Total Base Number	ASTM D2896	mgKOH/g	5.5
Sulphated Ash	ASTM D874	% mass	1.1

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

## AVAILABLE PACK SIZES

IBC- 30006B, 205lt - 30006, 20lt - 32006