

PREMIUM GOLD 15W-40

PREMIUM GRADE ENGINE OIL MEETING API SN/CF

DESCRIPTION

Premium Gold is a versatile engine oil for petrol, light diesel and LPG engines requiring API SN/CF performance or lower including most modern cars. It is ideally suited to late model vehicles calling for a 15W-40 viscosity grade and provides excellent low temperature viscometrics.

SUMMARY OF BENEFITS

- Premium Gold 15W-40 fully meets the API SN and CF performance requirements, offering cost efficient rationalisation for some mixed fleets
- Premium Gold 15W-40 offers good soot control, reducing oil thickening and sludge deposits
- The 15W-40 viscosity provides wear protection at low ambient temperatures combining easy low temperature engine start-up and fast oil circulation to critical engine components, together with the high temperature protection provided by an SAE 40 Viscosity
- Can be used in both turbo and naturally aspirated engines
 - Suitable for multi valve engines
 - Suitable for LPG vehicles

SPECIFICATIONS

Premium Gold 15W-40 meets the following international performance specifications:

- SAE Viscosity 15W-40
- API SN/CF
- ACEA A2-96, B2-96
- Ford ESE- M2C -153E
- MIL-L-46152E, 2104E

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

PREMIUM GOLD 15W-40

PREMIUM GRADE ENGINE OIL MEETING API SN/CF

TYPICAL CHARACTERISTICS

PREMIUM GOLD	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8847
Kinematic Viscosity @ 40°C	ASTM D445	cSt	116
@ 100°C	ASTM D445	cSt	14.9
Viscosity Index	ASTM D2270	-	129
Pour Point	ASTM D97	°C	-27
Flash Point (COC)	ASTM D92	°C	200
Total Base Number	ASTM D2896	mgKOH/g	6.5
Sulphated Ash	ASTM D874	% mass	1.2

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30021B, 205lt - 30021, 20lt - 32021, 6lt - 30621, 5lt - 30521, 1lt - 30121