



**GULF WESTERN OIL**  
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

# SOLVENT-BASED DEGREASER

*HIGH QUALITY HEAVY DUTY, SOLVENT BASED DEGREASER*

## DESCRIPTION

Solvent based degreaser designed to remove oil, grease and grime from engine parts, automotive applications, transport, lawn mowers, chain saws, concrete and much more.

## SUMMARY OF BENEFITS

- Blended with high-powered solvents and emulsifiers
- Mixable with water

## STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## HEALTH, SAFETY AND ENVIRONMENT

This product is classified as HAZARDOUS according to the criteria of Worksafe Australia. This product is classified as a Dangerous Good, class 3, Flammable Liquid, UN 1223, PG II according to the Australian Dangerous Goods Code ADG7. This product is classified as a Poison, Schedule 5 according to the criteria of the NHMRC.

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

This product contains: KEROSENE 93% CAS 8008-20-6

Risk Phrases: R65 Harmful - may cause lung damage if swallowed

Safety Phrases: • S2 Keep out of reach of children • S23 Do not breathe vapour • S24 Avoid contact with skin • S62 If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label.

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

**Head Office:** 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

**Phone:** 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

**ACN:** 087 558 398



**GULF WESTERN OIL**  
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

# SOLVENT-BASED DEGREASER

HIGH QUALITY HEAVY DUTY, SOLVENT BASED DEGREASER

## TYPICAL CHARACTERISTICS

DEGREASER	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.80
Boiling Point	-	°C	155
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	N/A
@ 100°C	ASTM D445	cSt	N/A
Viscosity Index	ASTM D2270	-	-
Pour Point	ASTM D97	°C	-30
Flash Point (COC)	ASTM D92	°C	>42
Colour	ASTM D1500	-	Clear Blue

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

## AVAILABLE PACK SIZES

205lt - 40008, 20lt - 42008

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

**Head Office:** 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

**Phone:** 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

**ACN:** 087 558 398