



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

SUPERTAK

PROTECTS CHAINS AND BARS OF HIGH PERFORMANCE CHAIN SAWS

DESCRIPTION

Gulf Western Supertak Chain Bar Oil protects bars and chains of high performance chain saws. Contains anti-wear additives and tackifiers to protect the bar and chain and minimise "throw-off" from the chain.

SUMMARY OF BENEFITS

- Excellent adhesion to the chain and bar
- High level of protection ensures longer bar and chain life
- Provides good antirust and storage protection
- Good penetration of chain links

SPECIFICATIONS

Supertak meets the following international performance specifications:

- ISO VG 150

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398

SUPERTAK

PROTECTS CHAINS AND BARS OF HIGH PERFORMANCE CHAIN SAWS

TYPICAL CHARACTERISTICS

SUPERTAK	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.865
Kinematic Viscosity @ 40°C	ASTM D445	cSt	150
@ 100°C	ASTM D445	cSt	20
Viscosity Index	ASTM D2270	-	>150
Pour Point	ASTM D97	°C	-12
Flash Point (COC)	ASTM D92	°C	>220

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30080B, 205lt - 30080, 20lt - 32080, 4lt - 30480 and 1lt - 30180