

SYN-X 4000 5W-30

LOW VISCOSITY, FULL SYNTHETIC ENGINE OIL MEETING SN/GM DEXOS 1/ILSAC GF-5

DESCRIPTION

Syn-X 4000 is a high performance, GM Dexos 1 engine oil. It has been designed to provide excellent fuel efficiency and minimal engine wear, particularly at cold start ups and is formulated using the latest in API additive technology. Syn-X 4000 is suitable for vehicles using petrol, LPG and diesel fuels including light and moderately loaded diesel engines calling for a 5W-30 or 10W-30.

Syn-X 4000 has been designed for use where the engine manufacturer recommends low viscosity oil such as a 5W-30, 7.5W-30 or a 10W-30. Syn-X 4000 is suitable for most passenger cars manufactured from 1980 onwards calling for SN or earlier API grades. Syn-X 4000 meets ILSAC GF-5 and GM Dexos1 specifications.

SUMMARY OF BENEFITS

- Full Synthetic formulation
- Superior Energy Conserving specification, GF-5
- Super extended drain intervals surpassing any mineral based lubricant
- Excellent soot and sludge control resulting in cleaner engines
- Outstanding low temperature viscometrics for reduced wear at start up

SPECIFICATIONS

Syn-X 4000 5W-30 meets the following international performance specifications:

- SAE Viscosity 5W-30
- GM Dexos1
- API SN / ILSAC GF-5

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

SYN-X 4000 5W-30

LOW VISCOSITY, FULL SYNTHETIC ENGINE OIL MEETING SN/GM DEXOS 1/ILSAC GF-5

TYPICAL CHARACTERISTICS

SYN-X 4000 5W-30	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8590
Kinematic Viscosity @ 40°C	ASTM D445	cSt	60
@ 100°C	ASTM D445	cSt	11
Viscosity Index	ASTM D2270	-	>150
Pour Point	ASTM D97	°C	-34
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	8.5
Sulphated Ash	ASTM D874	% mass	<1.00

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 60001, 20lt - 62001, 5lt - 60501