

## ULTRA SHIFT M SYNTHETIC MANUAL TRANS FLUID 75W

### FULL SYNTHETIC MANUAL TRANSMISSION FLUID

#### DESCRIPTION

ULTRA SHIFT M SYNTHETIC MANUAL TRANS FLUID 75W is a full synthetic higher performance manual transmission fluid specifically designed to meet the requirements of manual transmission and dry-clutch type dual clutch transmissions.

#### SUMMARY OF BENEFITS

- Full Synthetic formulation offering enhanced gear protection across a wide temperature range.
- Super oxidation stability allowing longer service life and better protection against deposit formation.
- Excellent viscosity retention due to use of a premium viscosity modifier, providing a high level of gear protection across the service drain interval.
- Low viscosity formulation helps improve fuel economy through reduction in friction and churn losses in the transmission.
- Advanced additive package extends the life of synchronisers and allows smoother shifting performance.
- Suitable for both manual transmissions calling for SAE 75W and dry-clutch type DCT transmissions calling for a SAE 75W fluid.

#### SPECIFICATIONS

ULTRA SHIFT M SYNTHETIC MANUAL TRANS FLUID 75W meets the requirements of the following transmission specifications:

- API GL-4
- SAE 75W
- FORD M2C-200-D2
- BMW MTF L-1, -2, -3, -4
- MB 228.10
- VW G 052 171, G 052 178, G 052 512, G 052 527, G 052 726, G 055 726, G 060 726, G 070 726

#### STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**ULTRA SHIFT M SYNTHETIC MANUAL TRANS FLUID 75W**  
*FULL SYNTHETIC MANUAL TRANSMISSION FLUID*

**TYPICAL CHARACTERISTICS**

ULTRA SHIFT M SYNTHETIC MANUAL TRANS FLUID 75W	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.852
Kinematic Viscosity @ 40°C	ASTM D445	cSt	30.9
@ 100°C	ASTM D445	cSt	6.08
Viscosity Index	ASTM D2270	-	149
Pour Point	ASTM D97	°C	-45
Flash Point (COC)	ASTM D92	°C	210
Brookfield Viscosity -40°C	ASTM D2983	cP	64,600

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**AVAILABLE PACK SIZES**

60lt - 360062, 20lt - 320062, 4lt - 304062