

AGRIBLUE 10W-30

**FORMULATED WITH VPI. SEMI-SYNTHETIC.
PREMIUM UNIVERSAL TRACTOR TRANSMISSION OIL**

DESCRIPTION

Agriblue is a semi-synthetic high performance UTTO - Universal Tractor Transmission Oil - suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches and brakes. The anti-squawk additive ensures effective operation of wet brakes. This highly boosted formulation was developed for high horsepower tractors operating in severe applications. Agriblue has been specifically developed to meet a wide range of specifications from the world's leading tractor and hydraulic pump OEM's.

Gulf Western Oil's additive technology results in a high level of wear protection, very low foaming tendency and has been successfully used in millions of tractors from around the world. The highly shear stable formulation ensures protection across the whole drain interval and in the harshest farming environments. Agriblue is formulated with a vapour phase inhibitor VPI which protects equipment in storage against corrosion from atmospheric moisture.

*VPI: Vapor Phase Inhibitor is blended into Agriblue to provide all year round protection against atmospheric corrosion. During long periods of inactivity, the VPI in Agriblue will form a protective vapor shield over gear teeth and other components that are exposed to the atmosphere protecting against rust and corrosion.

SUMMARY OF BENEFITS

- Significantly increased gear wear protection
- Correct frictional characteristics ensure quiet wet brake operation
- Proven field performance
- Good anti-foam characteristics
- Based on borate technology
- Excellent shear stability performance is maintained and very high thermal/oxidation stability provide long fluid life
- Good water tolerance ensures hydraulic performance is maintained
- Low Copper activity
- Good filterability
- Excellent anti-squawk properties
- High level corrosion protection during out of season storage

SPECIFICATIONS

• API GL-4 • SAE 10W-30 (Table J300) • SAE 80 GEAR OIL (Table J306)

HYDRAULIC PUMP PERFORMANCE

Sperry Vickers/Eaton I-286-S (industrial)

M-2950-S (mobile) & I-280-S

Denison HF-0, HF-1, HF-2

Sauer Sundstrand/Danfoss Hydraulics Hydro Static Trans Fluid

Cincinnati Milacron P-68, P-69, P-70

ZF: TEML03, TEML06

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398

AGRIBLUE 10W-30

FORMULATED WITH VPI. SEMI-SYNTHETIC.
PREMIUM UNIVERSAL TRACTOR TRANSMISSION OIL

SPECIFICATIONS (CONTINUED)

JOHN DEERE

J20C, J20D (factory fill), HYGUARD, Quatrol®

NEW HOLLAND FORD
(New Holland Group)

ESN-M2C134-A, B, C, D (FNHA-2-C-201.00)
M2C (A TO C)
M2C86 (A TO C) , M2C43, M2C92-A, M2C53-B
M2C77-A, M2C53-A, M2C48-B & C, M2C41-B
FNHA-2-C-200.00* FNHA-2-C-200A
(Super All Season Driveline and hydraulic fluid - F200-a)
(*Winter Grade
M2C134-D/FNHA 201.00
NB 410B
MAT 3540, MAT 3525, MAT 3526 (CURRENT)
I-286-S (VICKERS), M-2950-S (VICKERS)

MASSEY FERGUSON

M-1141 (EP trans fluid)
M-1135 (trans / hydraulic - Europe)
M-1143 (trans / hydraulic - Europe)
M-1145
M-1127A and M-1127B
M-1110
M-1129A

CASE CORP (JI Case and International
Harvester)

JIC-143, JIC-144, JIC-145, JIC-185
MS-1210
MS-1204
MS-1205
MS-1206 (POWERGUARD PFT)
MS-1207 (HY-TRANS PLUS)

AGRIBLUE 10W-30

FORMULATED WITH VPI. SEMI-SYNTHETIC.
PREMIUM UNIVERSAL TRACTOR TRANSMISSION OIL

SPECIFICATIONS (CONTINUED)

MS - 1209
B5, B6
White Farm Q1826, Q-1705, Q-1766, Q-1802
AGCO, Powerfluid 821XL
Steiger: HYDR TRANS FLUID, SEMS 17001
Versatile
Deutz-Allis 25743 (PF-821 XL), 25741, 246634
Fiat-Hesston AF-87
NB 410B
MAT 3525

KUBOTA

UDT Hydraulic Fluid (UTF)

WHITE FARM (Oliver)

Q-1826 Hydraulic transmission fluid (HTF), 1802
Q1705, 1722, 1766, 1766B (UTHF), TYPE 55, 5J, Q1802

AGCO / Duetz-Allis / Allis-Chalmers

Power Fluid 821 XL

VALTRA

G2-08 (XT-60)

Landini

Tractor II Hyd

Allison

C2, C3, C4

Caterpillar

TO-2

Sperry Vickers

M-2950-S, I-286-S Ind

Clarke

TA-12, TA-18, HR500, HR600

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au

ACN: 087 558 398

AGRIBLUE 10W-30

FORMULATED WITH VPI. SEMI-SYNTHETIC.
PREMIUM UNIVERSAL TRACTOR TRANSMISSION OIL

SPECIFICATIONS (CONTINUED)

API	GL-4
CNH Case/New Holland	MAT 3525, FNHA-2-C-201
Volvo CE	WB-101
ZF	TE-ML 03E, TE-ML 03F, TE-ML 05F, TE-ML 06K, TE-ML 05E
Deutz-Allis	272843, 257541, 246634
Versatile	Specification 23M or 24M (Versatile)
Hesston-Fiat (tractors only)	AF-87, Multi-F, Multi-G (Current)
Komatsu Dresser	KES 07.866 (AXO 80), B-06-0001 and B-06-0002
Renk Doromat	873, 874 A and 874 B (Current)

AGRIBLUE 10W-30

FORMULATED WITH VPI. SEMI-SYNTHETIC.
PREMIUM UNIVERSAL TRACTOR TRANSMISSION OIL

RECOMMENDED FOR USE IN THE FOLLOWING OEM AGRICULTURAL EQUIPMENT (7)

API GL-4 (4)	Lamborghini
Argo S.p.A	Landini S.p.A (part of Argo S.p.A)
Arvin Meritor	Laverda (part of Argo S.p.A)
Belarus	Leyland
Buhler	Link Belt
Clark	Mahindra
Claas	McCormick (part of Argo S.p.A)
CNH MS 1209, MAT 3505	Mitsubishi Poclain
David Brown (part of CNH)	Renk
Denison HF-0, HF-1 & HF-2 (current) (6)	Rockwell Transmissions
DEXRON and Type A, Suffix A (tractor)	Same Deutz-Fahr
Eaton Hydraulics	Sauer Sundstrand
Ebru	Schluter
Fendt	Steiger
Ford ESN-M2C86-B and ESN-M2C86-C (5)	Steyr Daimler
Fort and Pegoraro (part of Argo S.p.A)	Sundstrand Hydraulics (Plessey)
Gleaner (part of AGCO)	Taylor
Hurlimann	Universal
Ingersoll Rand	Ursus
IMT	Valmet
International Harvester	Valpadana (part of Argo S.p.A)
International Hough (Dresser)	Valtractores
JCB	Versatile
JI Case	Vickers Hydraulics
KH Duetz	Volvo
Kioto	Yanmar
Komatsu and Komatsu / Dresser	Zetor
Kubota	

AGRIBLUE 10W-30

**FORMULATED WITH VPI. SEMI-SYNTHETIC.
PREMIUM UNIVERSAL TRACTOR TRANSMISSION OIL**

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TYPICAL CHARACTERISTICS

AGRIBLUE 10W-30	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.863
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	67.3
@ 100°C	ASTM D445	cSt	10.0
@ 100°C (after KRL 20hr)	CEC L-45-A-99	cSt	8.25
Viscosity Index	ASTM D2270	-	132
Pour Point	ASTM D97	°C	-36
Flash Point (COC)	ASTM D92	°C	210

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30048B, 205lt - 30048, 20lt - 32048