

EURO FORCE 5W-30

FULL SYNTHETIC, ULTRA LOW SAPS, ACEA C4 PASSENGER CAR DIESEL OIL

DESCRIPTION

Euro Force is a fully synthetic high performance, ultra-low SAPS passenger car engine oil for use in diesel and some petrol fuelled cars that specifically call for an ACEA C4, Ford M2C934-B or Renault RN 0720 specifications. Applications include selected Nissan (Navara/Pathfinder), Samsung, Land Rover, Suzuki, Renault and Jaguar where ACEA C4 is called for. May be used where ACEA C1 is called for. Euro Force is a high quality formulation will maximise DPF life, maximises fuel economy and helps extend drain intervals.

Note: Euro Force should only be used where it is specifically recommended by Gulf Western Oil or where an ACEA C4 specification is called for. Euro Force is a highly specialised formulation that may not be suitable for many modern passenger cars that do not call for an ACEA C4 rated oil. Not suitable for use where an ACEA C2 or C3 specification is recommended.

SUMMARY OF BENEFITS

- Ultra-Low sulphated ash content (<0.50%/wt)
- Fully Synthetic European formulation
- Low Zinc (<0.055%/Wt) and low Phosphorus (<0.050%/Wt) formulation
- Environmentally friendly formulation
- Maximises fuel economy
- Excellent thermal stability and low temperature performance
- Offers excellent catalyst protection (Diesel Particulate Filter)
- Specifically designed for vehicles calling for an ACEA C4 specification

SPECIFICATIONS

Euro Force meets the following international performance specifications:

- ACEA C4 - 2010
- Ford M2C934-B
- Renault RN 0720
- SAE 5W-30

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

EURO FORCE 5W-30

FULL SYNTHETIC, ULTRA LOW SAPS, ACEA C4 PASSENGER CAR DIESEL OIL

TYPICAL CHARACTERISTICS

EURO FORCE	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.88
Kinematic Viscosity @ 40°C	ASTM D445	cSt	60
@ 100°C	ASTM D445	cSt	10
Viscosity Index	ASTM D2270	-	>165
Pour Point	ASTM D97	°C	-34
Total Base Number	FTIR	mgKOH/g	6.02
Sulphated Ash			<0.50

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

20lt - 62007 and 5lt - 60507