

EURO ULTRA 5W-30

FULL SYNTHETIC, ULTRA LOW SAPS, ACEA C1 PASSENGER CAR DIESEL OIL

DESCRIPTION

Euro Ultra is a fully synthetic high performance, ultra-low SAPS passenger car engine oil for use in diesel and some petrol fuelled cars that specifically call for an ACEA C1 or DL-1 rated oil such as some Mazda, Ford, Mitsubishi and Citroen diesels fitted with Diesel Particulate Filters (DPF's). Euro Ultra is a high quality formulation will maximise DPF life, maximises fuel economy and helps extend drain intervals.

Note: Euro Ultra should only be used where it is specifically recommended by Gulf Western Oil or where an ACEA C1 specification is called for. Euro Ultra is a highly specialised formulation that may not be suitable for many modern passenger cars that do not call for an ACEA C1 rated oil. Not suitable for use where an ACEA C2, C3 or C4 specification is recommended.

SUMMARY OF BENEFITS

- Ultra-Low sulphated ash content (<0.50%/wt)
- Fully Synthetic European formulation
- Low Zinc (<0.055%/Wt) and low Phosphorus (<0.050%/Wt) formulation
- Environmentally friendly formulation
- Maximises fuel economy
- Excellent thermal stability and low temperature performance
- Offers excellent catalyst protection (Diesel Particulate Filter)
- Specifically designed for vehicles calling for an ACEA C1 or DL-1 specification

SPECIFICATIONS

Euro Ultra meets the following international performance specifications:

- ACEA C1 - 2007
- DL-1
- SAE 5W-30

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

EURO ULTRA 5W-30

FULL SYNTHETIC, ULTRA LOW SAPS, ACEA C1 PASSENGER CAR DIESEL OIL

TYPICAL CHARACTERISTICS

EURO ULTRA	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.88
Kinematic Viscosity @ 40°C	ASTM D445	cSt	60
@ 100°C	ASTM D445	cSt	10
Viscosity Index	ASTM D2270	-	>165
Pour Point	ASTM D97	°C	-34
Total Base Number	FTIR	mgKOH/g	6.02
Sulphated Ash			<0.50

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

20lt - 62008 and 5lt - 60508