



LAWNMOWER OIL

4 STROKE SAE 30 LAWMOWER ENGINE OIL

DESCRIPTION

Lawnmower Oil is an SAE 30 engine oil designed for the crankcases of small 4 stroke petrol engines. Ideally suited for those engines where the manufacturer specifies a mono grade SAE 30 oil.

SUMMARY OF BENEFITS

- Lawnmower Oil is a cost efficient oil for lawnmower engines or those requiring API SF/CC or lower performance

SPECIFICATIONS

Lawnmower Oil meets the following international performance specifications:

- SAE Viscosity 30
- API SF/CC

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

LAWNMOWER OIL

4 STROKE SAE 30 LAWMOWER ENGINE OIL

TYPICAL CHARACTERISTICS

LAWNMOWER OIL	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.878
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	95
@ 100°C	ASTM D445	cSt	11
Viscosity Index	ASTM D2270	-	105
Pour Point	ASTM D97	°C	-18
Flash Point (COC)	ASTM D92	°C	224
Total Base Number	ASTM D2896	mgKOH/g	5.5
Sulphated Ash	ASTM D874	% mass	1.1
Appearance	-	-	Clear Red Free Flowing

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 30084, 20lt - 32084, 1lt - 30184