



**GULF WESTERN**  
THE TOUGH AUSTRALIAN

PRODUCT DATA

# Mineral Compressor Series

Multi Purpose Mineral Compressor Oil

## Description

The Compressor Series is a premium quality mineral, multi purpose range of compressor oils. Formulated for use in rotary vane, reciprocating, axial and screw air compressors

Note: Not suitable for use in compressors producing air for breathing. It is available in ISO Viscosity Grades 46, 68 and 100.

## Summary of Benefits

- Formulated with state of the art additive packages incorporating the latest technology.
- Provides state of the art anti wear additives for longer component life.
- Provides good filterability and demulsibility important in rotary screw compressors, where separators are expensive.
- Provides good hydrolytic stability for protection from entrained moisture.

## Specifications

Mineral Compressor meets the requirements of most modern manufacturers of air compressors, including but not limited to:

- Atlas Copco -Model GA & GAU series
- Jaeger Machine Company rotary screw & vane
- Atlas Copco portable rotary screw XA XAH
- LeRoi Division
- Dresser Industries both portable & stationary (including no aluminum vanes)
- Meets DIN 51506 (VBL, VCL, VDL), ISO DP6521, (DAH/G)

# Mineral Compressor Series

Multi Purpose Mineral Compressor Oil

## Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

## Typical Characteristics

Grade:	Super Compressor		46	68	100
	Test Method	Units			
Density @ 15°C	ASTM D1298	kg/L	0.89	0.89	0.89
Kinematic Viscosity					
@ 40°C	ASTM D445	cSt	46	68	100
@ 100°C	ASTM D445	cSt	6.9	9	11
Viscosity Index	ASTM D2270	-	96	96	96
Pour Point	ASTM D97	°C	-6	-6	-6
Flash Point (COC)	ASTM D92	°C	212	218	242

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

### Pack Sizes Available:

46: IBC - 30085B, 205lt - 30085, 20lt - 32085

68: IBC - 30075B, 205lt - 30075, 20lt - 32075, 1lt - 30175



## GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: [sales@gulfwestern.com.au](mailto:sales@gulfwestern.com.au)

Web: [www.gulfwestern.com.au](http://www.gulfwestern.com.au)

ACN 087 558 398