

TORQUE OIL 10W

CATERPILLAR TO-4 DRIVE TRAIN OIL

DESCRIPTION

Torque Oil is a monograde Caterpillar TO-4 performance drive train fluid. The frictional performance of Torque Oil is superior to TO-2 approved fluids. Torque Oil 10W has been designed to extend the life and performance of all Caterpillar transmissions and hydraulic systems as well as those of Komatsu drive trains. Torque Oil 10W also meets the Allison C4 requirements. Torque Oil 10W is also suitable for use in hydraulic systems where a 10W or 15W hydraulic fluid is called for. Suited for some hydrostatic transmissions.

SUMMARY OF BENEFITS

- Outstanding frictional characteristics for optimum clutch life
- Excellent compatibility with both seals and frictional material
- Has the ability to control brake chatter, thus extending the life of wet brakes
- Enhanced wear protection leading to longer life

SPECIFICATIONS

Torque Oil 10W meets the following international performance specifications:

- SAE Viscosity 10W
- API GL-3
- Caterpillar T0-4
- Allison C4

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398

TORQUE OIL 10W

CATERPILLAR TO-4 DRIVE TRAIN OIL

TYPICAL CHARACTERISTICS

TORQUE OIL 10W	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8782
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	42
@ 100°C	ASTM D445	cSt	6.5
Viscosity Index	ASTM D2270	-	107
Pour Point	ASTM D97	°C	-27
Flash Point (COC)	ASTM D92	°C	219

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30047B, 205lt - 30047, 20lt - 32047