



**GULF WESTERN**  
THE TOUGH AUSTRALIAN

## PRODUCT DATA

# Two Stroke – Air Cooled

## Air-cooled 2-Stroke Motor Oil

### Description

Air Cooled Two Stroke Oil is a versatile high performance low ash engine oil for use in air-cooled 2-stroke motors. This product is formulated for use in oil injected and pre-mix systems.

Air Cooled Two Stroke Oil is recommended for 2-stroke lawn mowers, chain saws, brush cutters, motor bikes and other similar 2-stroke engine powered implements.

Note: This product is not suitable for use in outboard marine engines that call for a TCW 3. Two stroke pre-mix should not be stored for more than 3 months. The fuel should be stored in well-sealed steel cans or specially designed plastic containers.

### Summary of Benefits

Air Cooled Two Stroke Oil offers:

- Suitable for API TA, TB, TC requirements.
- Low ash formulation controls piston, port and plug cleanliness.
- Contains a diluent to aid mixing with leaded and unleaded petrol.

### Specifications

Air Cooled Two Stroke Oil meets the following international performance specifications:

- API TC
- JASO FC
- TISI

# Two Stroke – Air Cooled

Air-cooled 2-Stroke Motor Oil

## Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

## Typical Characteristics

Grade:	Air Cooled Two Stroke Oil		
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.8609
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	65.9
@ 100°C	ASTM D445	cSt	10
TBN	ASTM D2896	Mg KOH/g	1.1
Viscosity Index	ASTM D2270	-	155
Pour Point	ASTM D97	°C	-18
Flash Point (COC)	ASTM D92	°C	90
Sulphated	Ash ASTM D874	% mass	0.09
Colour			Green

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Size Available:

205lt - 30083, 20lt - 32083, 5lt - 30583, 1lt - 30183



## GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398