



TWO STROKE - AIR COOLED

HIGH PERFORMANCE LOW ASH ENGINE OIL

DESCRIPTION

Two Stroke - Air Cooled Oil is a versatile high performance low ash engine oil for use in air-cooled 2-stroke motors. This product is formulated for use in oil injected and pre-mix systems. Two Stroke - Air Cooled Oil is recommended for 2-stroke lawn mowers, chain saws, brush cutters, motor bikes and other similar 2-stroke engine powered implements. Recommended dilution is between 25:1 (200mL to 5L) to 50:1 (100mL to 5L), or as per manufacturers specifications.

Note: This product is not suitable for use in outboard marine engines that call for a TCW 3. The fuel should be stored in well-sealed steel cans or specially designed plastic containers.

SUMMARY OF BENEFITS

- Suitable for API TA, TB, TC requirements
- Low ash formulation controls piston, port and plug cleanliness
- Contains a diluent to aid mixing with leaded and unleaded petrol

SPECIFICATIONS

Two Stroke - Air Cooled meets the following international performance specifications:

- API TC
- JASO FC, FB
- TISI

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au

ACN: 087 558 398

TWO STROKE - AIR COOLED

HIGH PERFORMANCE LOW ASH ENGINE OIL

TYPICAL CHARACTERISTICS

TWO STROKE - AIR COOLED	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.865
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	66
@ 100°C	ASTM D445	cSt	9.4
TBN	ASTM D2896	Mg KOH/g	>1.1
Viscosity Index	ASTM D2270	-	>120
Pour Point	ASTM D97	°C	-18
Flash Point (COC)	ASTM D92	°C	>90
Sulphated Ash	ASTM D874	% mass	0.05
Colour	-	-	Green

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 30083, 20lt - 32083, 5lt - 30583 and 1lt - 30183