



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

ULTRA DRIVE 80W-90

SYNTHETIC FORTIFIED HEAVY DUTY FINAL DRIVE FLUID

DESCRIPTION

Gulf Western Ultra Drive is a synthetic fortified SAE 80W-90 manual transmission and final drive lubricant. It is designed for highly loaded applications working in extreme environments such as road trains and heavy duty earthmoving equipment.

SUMMARY OF BENEFITS

- Extremely strong film strength offering excellent lubrication between surfaces
- Minimises wear and wear and pitting between gear teeth
- Extremely shear stable
- Suitable for applications calling for both 80W-90 and 85W-140 viscosity grades
- Excellent performance in extreme temperatures
- Will not gel when exposed to condensation
- Smooth gear shifting in all temperature ranges
- Extended drain interval

SPECIFICATIONS

Ultra Drive 80W-90 meets the following international performance specifications:

- SAE Viscosity 80W-90
- API GL-5
- ZF TE-ML 05A, 07A, 16B/C/D, 17B, 19B
- DAF (where GL-5 axle lubricants are recommended for use)
- MAN 342 M-2
- Mack GO-J
- Renault (where GL-5 or MIL-PRF-2105E axle lubricants are recommended for use)
- MIL-PRF-2105E
- Scania STO 1:0
- Arvin Meritor 0-76D
- Iveco (where MIL-PRF-2105E axle lubricants are recommended for use)

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398

ULTRA DRIVE 80W-90

SYNTHETIC FORTIFIED HEAVY DUTY FINAL DRIVE FLUID

TYPICAL CHARACTERISTICS

ULTRA DRIVE 80W-90	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.89
Kinematic Viscosity @ 40°C	ASTM D445	cSt	200
@ 100°C	ASTM D445	cSt	20.5
Viscosity Index	ASTM D2270	-	120
Pour Point	ASTM D97	°C	-25
Flash Point (COC)	ASTM D92	°C	205
Colour	ASTM D1500	-	3.5

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30057B, 205lt - 30057, 20lt - 32057