

# XMP-3 20W-50

## MULTI-GRADE ENGINE OIL

### DESCRIPTION

XMP Motor Oil is a 20W-50 motor oil ideally suited to vehicles (1998 or earlier), requiring a petrol engine oil meeting API SH or lower. For newer vehicles requiring API SL oils, use Hi Tech Premium.

### SUMMARY OF BENEFITS

- Suitable for pre 1999 vehicles
- Low Phosphorus content will not harm catalytic converter exhaust systems
- Can also be used for lubrication of lightly loaded diesel engines

### SPECIFICATIONS

XMP-3 20W-50 meets the following international performance specifications:

- SAE Viscosity 20W-50
- MIL-L-46152B
- API SH, CD
- Ford ESE-M2C-153E
- GM 6048M

### STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

# XMP-3 20W-50

MULTI-GRADE ENGINE OIL

## TYPICAL CHARACTERISTICS

XMP-3	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8865
Kinematic Viscosity @ 40°C	ASTM D445	cSt	163
@ 100°C	ASTM D445	cSt	18.5
Viscosity Index	ASTM D2270	-	125
Pour Point	ASTM D97	°C	-16
Flash Point (COC)	ASTM D92	°C	>205

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

## AVAILABLE PACK SIZES

205lt - 30022, 20lt - 32022 and 4lt - 30422