



GULF WESTERN
THE TOUGH AUSTRALIAN

PRODUCT DATA

Powertrain Fluid 60 CAT FD-1

Heavy Duty Final Drive and Axle Lubricant

Description

Powertrain Fluid 60 is an extreme pressure, heavy duty lubricant recommended for final Caterpillar drives and axles. Gulf Western Powertrain Fluid is available in SAE viscosity grade 60.

Summary of Benefits

- Gulf Western Powertrain Fluid protects Caterpillar final drives and axles in severe load applications
- Excellent resistance to foaming and corrosion
- Extreme pressure additives impart high load carrying capacity to the oil.

Specifications

Gulf Western Powertrain Fluid meets the following performance specifications:

- SAE 60 Viscosity
- CAT FD-1
- CAT TO-4

Powertrain Fluid 60 CAT FD-1

Heavy Duty Final Drive and Axle Lubricant

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Gear Oil	60	
Product Code:	60005		
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.90
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	270
@ 100°C	ASTM D445	cSt	22
Viscosity Index	ASTM D2270	-	100
Pour Point	ASTM D97	°C	-30
Flash Point (COC)	ASTM D92	°C	>200

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398