

CLEARONOX

DIESEL EXHAUST FLUID FOR SCR OF EXHAUST EMISSIONS

DESCRIPTION

Gulf Western Clearonox is a 32.5% solution of high purity urea in demineralised water, also known as AdBlue®. The product reduces exhaust emission levels of nitrogen oxide products (NOx) from diesel engines.

Clearonox is Australian manufactured and meets or exceeds the ISO 22241 international standard. Gulf Western Diesel Clearonox can be used in all Selective Catalytic Reduction (SCR) engines.

TYPICAL CHARACTERISTICS

Appearance:	Colourless Liquid
pH:	9-10
Density:	1.09g/mL

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

SUMMARY OF BENEFITS

- Reduces NOx emissions
- Improves fuel efficiency
- Complies with EURO 4, 5 and 6 standards

USAGE

Add Clearonox to the SCR storage tank only, do not overfill or cross-contaminate. Usual consumption is around 5 litres of Clearonox for every 100 litres of diesel fuel.



CLEARONOX

DIESEL EXHAUST FLUID FOR SCR OF EXHAUST EMISSIONS

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

205lt - 40078, 20lt - 42078