

EURO-SYN 10W-40

FULL SYNTHETIC, ULTRA HIGH PERFORMANCE (XHPD) DIESEL OIL

DESCRIPTION

Euro-Syn Long Drain is a fully synthetic ultra high performance heavy duty diesel engine oil. Euro-Syn Long Drain meets and complies with the demanding requirements of Euro I, II, III & IV exhaust emission legislation. It is ideally suited to European engines requiring SHPD level of performance. Euro-Syn is also suitable for American and Japanese diesels calling for CJ-4 performance level.

SUMMARY OF BENEFITS

- Full synthetic formulation
- Super extended drain intervals surpassing any mineral or American diesel type lubricant
- Excellent soot and sludge control resulting in cleaner engines
- Reduces fuel consumption due to superior technology
- Outstanding low temperature viscometrics for reduced wear at start up
- Dedicated European formulation
- Excellent mixed fleet oil
- Suitable for European, American and Japanese diesel engines

SPECIFICATIONS

Euro-Syn meets the following international performance specifications:

- ACEA E9-12 (2012)
- ACEA E7-12 (2012)
- ACEA E6-12 (2012)
- ACEA E4-12 (2012)
- API CJ-4
- MB-Approval 228.51/228.31
- MAN M 3477, MAN M 3271-1, MAN M 3575
- MTU Type 3.1
- MTU CAT - 2
- Volvo VDS-3/4
- Renault RVI RLD-2/RLD-3
- Renault Truck RGD
- Mack EO-N/EO-O Premium Plus
- Cummins CES 20076, 20077, 20081
- CAT ECF-3a
- Deutz DQC IV-10 LA
- Scania Low Ash
- JASO DH-2

EURO-SYN 10W-40

FULL SYNTHETIC, ULTRA HIGH PERFORMANCE (XHPD) DIESEL OIL

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TYPICAL CHARACTERISTICS

| EURO-SYN | Test Method | Units | Results |
|-------------------------------|-------------|---------|---------|
| Density @ 15°C | ASTM D1298 | kg/L | 0.8769 |
| Kinematic Viscosity @ 40°C | ASTM D445 | cSt | 94 |
| @ 100°C | ASTM D445 | cSt | 15.9 |
| Viscosity Index | ASTM D2270 | - | 170 |
| Pour Point | ASTM D97 | °C | -34 |
| Flash Point (COC) | ASTM D92 | °C | 210 |
| Total Base Number | ASTM D2896 | mgKOH/g | 7.7 |
| Sulphated Ash | ASTM D874 | % mass | <1.00% |

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30009B, 205lt - 30009 and 20lt - 32009