

POWER STEERING FLUID

AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

A power steering fluid designed that can be used in automatic transmissions where Dexron® III, Dexron® II or Mercon® fluids have been specified. It is also commonly used as a power steering fluid. It is suitable for use with new technology transmission components and meets the need for improved fluid stability and reliability under increased operating temperature.

SUMMARY OF BENEFITS

- Approved for a wide range of automatic and hydraulic transmissions
- Cost effective option to Dexron® III products
- May be used for service fill or top up where Dexron® II, Dexron® III and Mercon® fluids are specified
- The excellent detergency of this fluid keeps the power steering system clean and operating properly
- Helps prevent high-temperature steering fade and helps prevent difficult low-temperature steering
- Greatly improved low temperature properties for smooth cold shifts
- Excellent shear stability for long fluid and component life
- Has unsurpassed retention of frictional coefficient, for consistently smooth gear changes

SPECIFICATIONS

Power Steering Fluid meets the following international performance specifications:

- General Motors
- Dexron® III (F30556)
- Caterpillar TO-2
- Allison C4
- Ford Mercon®

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

POWER STEERING FLUID

AUTOMATIC TRANSMISSION FLUID

TYPICAL CHARACTERISTICS

POWER STEERING	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8626
Kinematic Viscosity @ 40°C	ASTM D445	cSt	50
@ 100°C	ASTM D445	cSt	8.8
Viscosity Index	ASTM D2270	-	>160
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D92	°C	>205
Colour	-	-	Red

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

1lt - 30111