

DESCRIPTION

TOP DOG GLOBAL™ PLUS is a synthetic premium diesel engine oil meeting the latest in lubrication technology. It is formulated with high quality synthetic base oil. It meets the specifications of nearly all modern engine manufacturers and OEM's. Due to its excellent dispersant properties TOP DOG GLOBAL™ PLUS is ideally suited for Series 60 Detroit Diesel and engines fitted with EGR (Exhaust Gas Recirculation) systems and those fitted with diesel particulate filters (DPF's). Its ideal application is as a true all fleet universal diesel oil. Top Dog Global™ Plus can be used in stationary engines, earthmoving and road transport applications as well as light commercial diesel applications and Allison C4 transmissions.

SUMMARY OF BENEFITS

- Extended drain intervals for more up time. (Meets Volvo VDS-4 extended drain intervals)
- Synthetic, providing fuel saving capability
- Synthetic, providing reduced oxidation and viscosity breakdown
- Suitable for Diesel Particulate Filters (DPF's) and engine fitted with Exhaust Gas Recirculation
- Superior sludge and soot control for a cleaner engine
- Reduced oil consumption
- Greatly reduced engine wear giving extended engine life
- Very good low temperature viscometrics for reduced wear at start up
- Low SAPS formulation (Sulfated Ash, Phosphorus and Sulfur)

SUITABLE FOR



SPECIFICATIONS

- SAE VISCOSITY 10W-40
- API CJ-4/SN, CI-4 PLUS, CI-4, CH-4
- ACEA E11, E7
- JASO DH-2
- CUMMINS CES 20081, 20078, 20077, 20076
- MACK EO-O PREMIUM PLUS
- MERCEDES BENZ 228.31
- VOLVO VDS-3, VDS-4
- ALLISON C4
- CATERPILLAR ECF-3, ECF-2, ECF-1, TO-2
- MTU TYPE 2.1
- DETROIT DIESEL DDC 93K218, SERIES 60, SERIES 2000/4000 TYPE 1
- MAN 3575
- RENAULT TRUCK RLD/RLD-2, RLD-3
- FENDT DQC 111-10 LA

TOP DOG GLOBAL PLUS	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.86
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	96
@ 100°C	ASTM D445	cSt	15.5
VISCOSITY INDEX	ASTM D2270	-	149
APPARENT VISCOSITY @ -25°C	ASTM D5293	cP	6000
POUR POINT	ASTM D97	°C	-30
FLASH POINT (COC)	ASTM D92	°C	210
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	10
SULPHATED ASH	ASTM D874	% mass	<1.00

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

IBC - #30013B, 205LT - #30013, 20LT - #32013, 10LT - #31013, 5LT - #30513

April 2026