

# TECHNICAL DATA SHEET

# GULF 1 10W-60



## DESCRIPTION

Gulf 1 is a fully synthetic premium petrol engine / light diesel oil designed for car enthusiast looking for ultimate engine protection. It is formulated with high performing synthetic base oil. It meets the latest specifications of all modern engine manufacturers and OEM's. It provides exciting performance characteristics and all season protection, controlling low temperature sludge and high temperature oxidation. Recommended for: Street machines/racing and high performance race cars, LPG or CNG fueled vehicles, all diesel engine light commercials and cars and cars running multi valve engines.

## SUMMARY OF BENEFITS

- Extended drain intervals for more up time
- Fully synthetic providing fuel saving capability
- Fully synthetic providing reduced oxidation and viscosity breakdown
- Superior sludge and varnish control for a cleaner engine
- Reduced oil consumption due to improved volatility control
- Greatly reduced engine wear giving extended engine life
- Very good low temperature viscometrics for reduced wear at start up

## SPECIFICATIONS

- SAE VISCOSITY 10W-60
- API SP/CF
- ACEA A3/B4

## SUITABLE FOR



GULF 1 10W-60	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.8584
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	130
@ 100°C	ASTM D445	cSt	>21.9
VISCOSITY INDEX	ASTM D2270	-	170 min
POUR POINT	ASTM D97	°C	-30
FLASH POINT (COC)	ASTM D92	°C	210
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	7
SULPHATED ASH	ASTM D874	% mass	<1.15

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

## STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

## AVAILABLE PACK SIZES

IBC - #30034B, 205LT - #30034, 5LT - #30534

January 2023

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747  
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au