

**DESCRIPTION**

Syn-X 3000 10W-40 is a premium blend synthetic motor oil suitable for most Australian, US, European and Asian engines calling for a SAE 10W-40 or 15W-40 engine oil with API SP/CF or earlier performance levels. Formulated using a combination of synthetic base oils and a modern additive package meeting the API SP/CF and ACEA A3/B4 performance requirements. May also be used in motorcycles with wet clutch operation and is a highly versatile engine oil that can be used in a wide range of operating conditions including severe, modern stop-start driving conditions. Recommended for: Cars, vans, utility vehicles and 4WD engines whether naturally aspirated or turbo charged running on Unleaded Petrols, LPG or diesel fuel. Suitable for use in motorcycle applications including those with wet clutch.

**SUMMARY OF BENEFITS**

- Excellent flow and pumpability on cold start
- Meeting the latest global API technology
- Synthetic base oil offers reduced oxidation and improved viscosity control
- Superior sludge and varnish control for a cleaner engine
- Reduced oil consumption due to improved volatility control
- Greatly reduced engine wear giving extended engine life
- High shear strength and excellent volatility

**SPECIFICATIONS**

- SAE 10W-40
- API SP/CF
- ACEA A3/B3/B4
- MB 229.3
- VW 502.00/505.00
- RENAULT RN0700/RN0710
- CHRYSLER MS 6395
- GM 6094M
- JASO MA2

**SUITABLE FOR**



SYN-X 3000 10W-40	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.861
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	101
@ 100°C	ASTM D445	cSt	15.0
VISCOSITY INDEX	ASTM D2270	-	155
POUR POINT	ASTM D97	°C	-34
FLASH POINT (COC)	ASTM D92	°C	>224
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	10.4

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

205LT - #30037, 20LT - #32037, 6LT - #30637, 5LT - #30537, 1LT - #30137

April 2026