

TECHNICAL DATA SHEET

AGRITRANS UTTF



DESCRIPTION

Agritrans UTTF is a multi purpose oil suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches and brakes. The anti squawk additive ensures effective operation of wet brakes. Agritrans UTTF has been specifically developed to meet a wide range of specifications from most modern tractor and hydraulic pump OEM's. Gulf Western's additive technology has been field tested in over 250 tractors and that combines to more than 200,000 hours of field tests.

SUMMARY OF BENEFITS

- Superior gear wear protection
- Correct frictional characteristics ensure quiet wet brake operation
- Proven field performance
- Good anti-foam characteristics
- Excellent shear stability and thermal/oxidation stability provide long fluid life
- Good water tolerance ensures hydraulic performance is maintained
- Low copper activity
- Good filterability
- Excellent anti-squawk properties

SUITABLE FOR



SPECIFICATIONS

- API GL-4
- SAE 10W-30 (Table J300)
- SAE 80W (Table J306)
- Case 1207, 1209
- Ford M2C-134D
- John Deere J20C
- Kubota UDT
- MF-1145
- New Holland MAT 3525, 3540
- Volvo WB101

For the full list of specifications, please visit our website - www.gulfwestern.com.au or call our technical line on 1800 248 919.

AGRITRANS	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.865
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	70
@ 100°C	ASTM D445	cSt	10.4
VISCOSITY INDEX	ASTM D2270	-	135
POUR POINT	ASTM D97	°C	-35
FLASH POINT (COC)	ASTM D92	°C	190

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

IBC - #30044B, 205L - #30044, 60L - #36044, 20L - #32044, 5L - #30544

March 2022

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au