

**DESCRIPTION**

Two Stroke - Air Cooled Oil is a versatile high performance low ash engine oil for use in air-cooled 2-stroke motors. This product is formulated for use in oil injected and pre-mix systems. Two Stroke - Air Cooled Oil is recommended for 2-stroke lawnmowers, chainsaws, brushcutters, motorbikes and other similar 2-stroke engine powered implements. Recommended dilution is between 25:1 (200mL to 5L) to 50:1 (100mL to 5L), or as per manufacturers specifications. Note: This product is not suitable for use in outboard marine engines that call for a TCW 3. The fuel should be stored in well-sealed steel cans or specially designed plastic containers.

**SUMMARY OF BENEFITS**

- Suitable for API TA, TB, TC requirements
- Low ash formulation controls piston, port and plug cleanliness
- Contains a diluent to aid mixing with leaded and unleaded petrol

**SPECIFICATIONS**

- API TC
- JASO FC, FB
- TISI

**SUITABLE FOR**



ATF DEX III	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.865
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	66
@ 100°C	ASTM D445	cSt	9.4
TBN	ASTM D2896	Mg KOH/g	>1.1
VISCOSITY INDEX	ASTM D2270	-	>120
POUR POINT	ASTM D97	°C	-18
FLASH POINT (COC)	ASTM D92	°C	>90
SULPHATED ASH	ASTM D874	% mass	0.05
COLOUR	-	-	Green

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

205LT - #30083, 20LT - #32083, 5LT - #30583 AND 1LT - #30183

February 2022