

DESCRIPTION

Solvent Based Degreaser designed to remove oil, grease and grime from engine parts, automotive applications, transport, lawn mowers, chain saws, concrete and much more.

SUMMARY OF BENEFITS

- Blended with high-powered solvents and emulsifiers
- Mixable with water

SOLVENT BASED DEGREASER	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.80
BOILING POINT	-	°C	155
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	N/A
@ 100°C	ASTM D445	cSt	N/A
VISCOSITY INDEX	ASTM D2270	-	-
POUR POINT	ASTM D97	°C	-30
FLASH POINT (COC)	ASTM D92	°C	>42
COLOUR	ASTM D1500	-	Clear Blue

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

205LT - #40008, 20LT - #42008