

TECHNICAL DATA SHEET

BRAKE CLEANER



DESCRIPTION

Gulf Western Brake Cleaner is a dynamic non chlorinated, non toxic cleaner aerosol designed to rapidly remove brake fluids, oils, dust, dirt, grease and other contaminants from brake linings, disc pads, drums, clutch plates, rotors, cylinders and springs. Stops squeal in disc brakes and can be applied without disassembly of brakes. Gulf Western Brake Cleaner dries super fast, which enables quicker brake partchanges. It also cleans other workshop equipment.

DIRECTIONS FOR USE

If possible lay rags or cardboard paper under the area where cleaning is to take place so as to contain residues resulting from the cleaning process and prevent them from entering drains and waterways. Shake the can well for a few seconds and apply liberally onto areas to be cleaned and allow to run off. Allow to air dry or dry by wiping the residues with a cloth. Repeat if necessary for thick deposits of contaminants to ensure complete removal.

CAUTION

Do not spray onto painted surfaces. If accidentally sprayed onto painted surfaces then remove immediately by washing with water. Do not allow this product to dry onto painted surface as it will lead to a streaky appearance. If this happens then polish the surface. Avoid applying onto bitumen surfaces or rubber as it is likely to soften such surfaces and render them sticky for long periods.

USAGE

Under normal usage the Gulf Western Brake Cleaner will provide up to 300 spray applications per 400 gram can. Usage will also be dependant on the duration of the spray.

WORKABILITY

Gulf Western Brake Cleaner contains active constituents that will rapidly soften and dissolve the strong bonding between the contaminants and the brake lining causing the contaminants to detach and run off. Gulf Western Brake Cleaner contains powerful reagents enabling penetration into narrow crevices and difficult to get to areas. Gulf Western Brake Cleaner is safe to use as a general purpose cleaner and is very effective at cleaning other workshop equipment including vices, tools, metal frames etc.

WARNING

Intentional misuse by deliberately concentrating or inhaling contents can be harmful or fatal. Keep in a cool dry place away from sun. Do not store above 50°C. Do not use near fire or naked flame. Do not incinerate this can even when empty. Dispose of waste residues and empty cans thoughtfully.

PROPELLANT

Hydrocarbon.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

840mL - # 68098

February 2024

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au