

COMP-R CLASSIC 15W-50

SEMI SYNTHETIC HIGH PERFORMANCE ENGINE OIL

DESCRIPTION

Comp-R Classic 15W-50 is a semi synthetic engine oil for high performance engines and classic vehicles where the owner wants to offer exceptional protection for their investment. Formulated with 40% synthetic base oil to offer excellent cold start protection as well as high temperature stability and sludge control. Additional seal conditioning agents to ensure seal materials in older engines are maintained properly to minimize leaks.

Exceeding API SL/CF and ACEA A3/B3 performance levels and boosted with additional anti-wear additives, Comp-R Classic 15W-50 has been designed to protect key engine components in high performance engines including those with flat tappet cams. Suitable for use in motorcycle applications with wet clutch as Comp-R Classic 15W-50 also meets JASO MA frictional requirements.

SUMMARY OF BENEFITS

- Semi Synthetic formulation offering enhanced temperature-viscosity characteristics compared to mineral oil
- High viscosity at operating temperature to protect the engine under load
- Superior oxidation stability compared to mineral oils
- Excellent engine cleanliness and sludge control
- Additional seal conditioners to reduce leakage in older engines
- Outstanding wear protection for older, flat tappet cam engines from high levels of Zinc and organic molybdenum compounds
- Compatible with most common race fuels
- Able to be used in motorcycle engines including those with a wet clutch

SPECIFICATIONS

Comp-R Classic 15W-50 meets the following specifications

- API SL/CF
- ACEA A3/B3
- JASO MA

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au

ACN: 087 558 398

COMP-R CLASSIC 15W-50

SEMI SYNTHETIC HIGH PERFORMANCE ENGINE OIL

TYPICAL CHARACTERISTICS

COMP-R CLASSIC	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.866
Kinematic Viscosity @ 40°C	ASTM D445	cSt	147
@ 100°C	ASTM D445	cSt	19.4
Viscosity Index	ASTM D2270	-	150
Pour Point	ASTM D97	°C	-27
Flash Point (COC)	ASTM D92	°C	240
Apparent Viscosity @ -20°C	ASTM D5293	mPa.s	5550
Anti-Wear Additives (Zinc + Moly)	ASTM D6481	ppm	1500ppm

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 300118 and 5lt - 305118