



DRILL ROD GREASE

HIGH QUALITY, MULTI PURPOSE GREASE

DESCRIPTION

Drill Rod Grease is a multipurpose grease for high temperature and anti-seize applications which has a smooth and tacky texture.

Drill Rod Grease is manufactured with Lithium complex base thickener, selected paraffinic Base Oils combined with Rust, Oxidation and Corrosion Inhibitors, tackiness adhesive additives, copper, graphite, zinc oxide, molybdenum disulphide and Extreme Pressure additives.

RECOMMENDATIONS

- Drill Rod Grease is designed for application to threads of drill rods to prevent seizing. It also provides maximum protection for tubing and casing connections in high pressure wells

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

DRILL ROD GREASE

HIGH QUALITY, MULTI PURPOSE GREASE

TYPICAL CHARACTERISTICS

DRILL ROD GREASE	Test Method	Results
NLGI	-	1.5
Colour	-	Grey/Black
Penetration @ 25°C -		
Worked, 60 Strokes	ASTM D217	295 min - 315 max
Dropping Point °C	ASTM D2265	250+
Water Washout @ 80°C, %	ASTM D1264	Less than 3.5
Leakage	ASTM D1263	1.5
Oxidation Stability Pressure -		
Drop @ 100 Hour, kPa	ASTM D942	15
Timken, OK Load Kg	ASTM D2509	27
4-Ball Weld, Kg/f	ASTM D2596	600
4-Ball Wear Scar, mm	ASTM D2266	0.45
Rust Prevention Characteristics	ASTM D1743	No Rust
Mineral Oil Viscosity cSt @ 40°C	ASTM D445	320

The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes.

AVAILABLE PACK SIZES

20kg - 62051

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398