



MOTO 4T 10W-40 SL

PREMIUM MOTORCYCLE ENGINE OIL

DESCRIPTION

MOTO 4T 10W-40 SL is formulated from premium base oils coupled with a highly effective additive package for the protection of motorcycle engines. MOTO 4T 10W-40 SL demonstrates excellent performance in the face of increasing demands of motorcycle engines.

Suitable for use in 4-stroke motorcycle engines requiring an API SL (or earlier) and JASO MA2 oil.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear
- Correct frictional characteristics for operation in motorcycles with wet clutch
- Shear stable formulation offering enhanced protection across the full oil drain

SPECIFICATIONS

Meets the following performance specifications:

- SAE - 10W-40
- API - SL
- JASO - MA2

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

MOTO 4T 10W-40 SL

PREMIUM MOTORCYCLE ENGINE OIL

TYPICAL CHARACTERISTICS

| MOTO 4T 10W-40 SL | Test Method | Units | Results |
|-----------------------------|-------------|----------|--------------------|
| Colour (visual) | - | - | Fluorescent yellow |
| Odour/Fragrance | - | - | Strawberry |
| Density @ 15°C | ASTM D7042 | kg/L | 0.866 |
| Colour | ASTM D1500 | - | 2.0 |
| Kinematic Viscosity @ 40°C | ASTM D7042 | cSt | 115.8 |
| Kinematic Viscosity @ 100°C | ASTM D7042 | cSt | 15.7 |
| Viscosity Index | ASTM D2270 | - | 143 |
| Apparent Viscosity @ -25°C | ASTM D5293 | cP | 6400 |
| Pour Point | ASTM D97 | °C | -36 |
| Flash Point (COC) | ASTM D92 | °C | 240 |
| Total Base Number | ASTM D2896 | mg KOH/g | 7.0 |

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

300152