

## **MULTI-LITH EP2**

### **GENERAL PURPOSE EXTREME PRESSURE GREASE**

#### **DESCRIPTION**

MULTI-LITH EP2 is a high quality lithium soap based grease for lubrication of plain roller and ball bearings as well as general automotive and chassis lubrication.

#### **SUMMARY OF BENEFITS**

- High degree of water resistance
- Excellent load carrying (extreme pressure) capability for medium to high loads
- High level of anti-wear performance
- Good adhesive properties means that the grease will stay in place allowing the protective film to provide lubrication and protection
- Highly versatile multi-purpose grease

#### **SPECIFICATIONS**

MULTI-LITH EP2 meets the following specifications

- NLGI Grade 2

#### **STORAGE**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### **HEALTH, SAFETY AND ENVIRONMENT**

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

## MULTI-LITH EP2

### GENERAL PURPOSE EXTREME PRESSURE GREASE

#### TYPICAL CHARACTERISTICS

MULTI LITH	Test Method	Results
Appearance	-	Smooth dark brown grease
NLGI classification	-	2
Thickener	-	Lithium
Base oil	-	Mineral
Base Oil Viscosity	ASTM D445	160 cSt
Worked penetration	ASTM D217	265 - 295
Dropping point (°C)	ASTM D566	185
Oil separation (%)	IP121	<5
Copper corrosion	IP112	Pass
Resistance to corrosion Emcor (a)	IP 220	0:0
Water washout @ 39°C %	ASTM D1264	3
Four Ball Weld Load (kgs)	IP 239	315
Operating temperature range	-	-20°C to 140°C

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

#### AVAILABLE PACK SIZES

20kg - 42035, 450gm - 40435