

# SYN-CVT FLUID

## MULTI-FUNCTIONAL SYNTHETIC UNIVERSAL CVT TRANSMISSION FLUID

### DESCRIPTION

Syn-CVT Fluid is a synthetic multi-functional transmission fluid suitable for use in most Continuously Variable Transmissions including those that are chain and belt driven.

Syn-CVT Fluid is comparable in quality to genuine CVT fluids however works across multiple vehicle makes and models making it a true universal fluid.

### SUMMARY OF BENEFITS

- Suitable for use in nearly all belt, chain and hybrid CVT's excluding some hybrid Toyota and hybrid Ford models
- Excellent shear stability for increased drain intervals
- Improved anti foam properties
- Advanced Anti Shudder durability
- Excellent metal to metal friction performance
- Excellent seal compatibility
- True multi-functional, universal CVT Fluid
- Synthetic formulation
- Excellent low and high temperature properties

### SPECIFICATIONS

Syn-CVT Fluid meets the following international performance specifications:

- Audi/VW (TL 52180, G 052 180, G 052 516)
- Dodge/Jeep (NS-2, CVTF+4)
- Ford (CVT30, Mercon C, CVT23)
- GM/Saturn (DEX-CVT)
- Honda (HMMF, HCF-2)
- Hyundai/Kia (SP-CVT 1)
- Mazda (CVTF, CVT3320)
- Mercedes Benz (236.20)
- Mini Cooper (EZL 799A)
- Mitsubishi (CVTF-J1, CVTF-J4)
- Nissan (NS-1, NS-2, NS-3)
- Subaru (NS-2/Lineartronic CVTF, K0425Y0710, CV-30, High Torque CVT Fluid)
- Suzuki (TC, NS-2, CVT Green 1, CVT Green 2)
- Toyota/Lexus (TC, FE)

# SYN-CVT FLUID

## MULTI-FUNCTIONAL SYNTHETIC UNIVERSAL CVT TRANSMISSION FLUID

### STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

### TYPICAL CHARACTERISTICS

SYN-CVT FLUID	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8570
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	33.7
@ 100°C	ASTM D445	cSt	7.19
Viscosity Index	ASTM D2270	-	184
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D92	°C	193
Colour	-	-	Red

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

### AVAILABLE PACK SIZES

20lt - 62041, 4lt - 60441