

SYN-TS™ ATF 10W

FULLY SYNTHETIC, MULTI FUNCTIONAL AUTOMATIC TRANSMISSION FLUID

DESCRIPTION

SYN-TS™ ATF is a fully synthetic ATF multi functional transmission fluid that is formulated to meet the requirements of most modern and older automatic transmissions. Suitable for extended drain intervals up to 150,000 km's for general use and 80,000km's for heavy duty applications. It covers a wide range of specifications making it a true multi functional product.

SUMMARY OF BENEFITS

- SYN-TS™ is suitable for use in ZF 6 Speed ZF6HP26 Transmissions
- Eliminates the requirement to stock additional fluids
- Suitable for older, modern and high performance applications
- Formulated with Enhanced frictions modifiers
- High VI
- Can be used where a Dexron® VI, III, IID,V1, Ford 95LE, Nissan J Matic Range, ATF +4, Mitsubishi SPii, SPiii and Allison C4 fluid is called for
- Excellent low temperature viscometrics
- GL-4 equivalent gear protection
- Decreased down time
- Extended drain intervals
- Excellent shear stability
- Minimal viscosity loss
- Greatly reduced wear
- Reduced oxidation
- Superior frictional properties
- Softer gear change
- Improved sludge and varnish control

SPECIFICATIONS

Syn-TS™ ATF 10W meets the following international performance specifications:

- Aisin Warner AW1
- Alison C4
- Alison TES - 295
- Audi G 052 162
- Audi G 052 990
- Audi G 052 025
- BMW 7045E
- BMW LA 2634
- BMW LT 71141
- Chrysler ATF, Mopar AS68RC
- Dexron, IID, E, III F, G, H
- Dexron VI
- Esso LT 71141
- Ford Type FNR5, 85le/95le
- Ford Mercon V
- Honda ATF Z1
- Hyundai SP II, SP III, SPH-IV
- Hyundai NWS-9638
- Idemitsu K17
- JASO 1-A
- JWS 3309, 3324

SYN-TS™ ATF 10W

FULLY SYNTHETIC, MULTI FUNCTIONAL AUTOMATIC TRANSMISSION FLUID

SPECIFICATIONS (CONTINUED)

- KIA SP II, SP III
- MAN 339F, V1, V2, Z1, Z2
- Mazda ATF M III, MV
- Mercedes 236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
- Mitsubishi SPII, SPIII
- Nissan Matic D, J, K, S
- Nissan 402
- Shell 3403, LA2634
- Subaru ATF, ATF-HP
- Texaco ETL 7045E
- Texaco ETL 8072B
- Toyota T-III, T-IV, WS (JWS 3324)
- Voith 55.6335.XX (G607)
- Voith 55.6336.XX (G1363)
- Volvo Passenger Car (4 – 6 sp)
- Volvo 97340, 97341
- VW 052 162
- VW 052 990
- VW 055 025
- ZF TEL ML 03D, 04D, 05L, 09, 11B, 14A, 14B, 16L, 17C, 20B

SYN-TS™ ATF also provides a GL-4 level of gear protection.

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

SYN-TS™ ATF 10W

FULLY SYNTHETIC, MULTI FUNCTIONAL AUTOMATIC TRANSMISSION FLUID

TYPICAL CHARACTERISTICS

SYN-TS ATF 10W	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8507
Kinematic Viscosity @ 40°C	ASTM D445	cSt	32
@ 100°C	ASTM D445	cSt	6.7
Viscosity Index	ASTM D2270	-	180 - 200
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D92	°C	224

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

IBC - 30058B, 205lt - 30058, 60lt - 36058, 20lt - 32058, 5lt - 30558, 1lt - 30158