



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

SYN-TS® LV

FULL SYNTHETIC LOW VISCOSITY MULTI-VEHICLE TRANSMISSION FLUID

DESCRIPTION

Syn-TS® LV is a low viscosity, technically advanced, full synthetic multi-vehicle automatic transmission fluid suitable for use as service fill in most low viscosity automatic transmission applications.

Proven performance through extensive field and laboratory testing to provide a service fill alternative to OEM fluids from US, European and Asian transmission manufacturers.

SUMMARY OF BENEFITS

- Eliminates the need to stock many OEM fluids
- Full Synthetic formulation offering enhanced temperature-viscosity characteristics and longer life
- Superior shear stable formulation for enhanced performance and smooth shifting throughout the fluid life
- Proven wear protection to enhance transmission life
- Excellent anti-shudder performance
- Improved sludge and varnish control
- Extended drain intervals may be possible
- Suited to both current and older automatic transmissions where Dexron VI, Chrysler ATF +4, Mercon LV, Toyota WS, Hyundai/Kia and Mitsubishi SP-IV are called for

SPECIFICATIONS

Service fill applications for the following specification number:

- Dexron VI
- Mercon LV
- Chrysler ATF +4
- JASO 1-A-LV
- Aisin Warner AW-1
- Honda DW-1
- Hyundai/Kia SP-IV, SPH-IV, SP-IV RR
- Mitsubishi ATF-J2, SP-IV
- Nissan Matic S
- Toyota WS (JWS 3324)
- Audi/VW G 055 005, G 055 162, G 060 162, G 055 540
- BMW 83 22 0 142516, 83 22 2 152 426 ZF 6, 8 and 9 speed transmissions

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

SYN-TS® LV

FULL SYNTHETIC LOW VISCOSITY MULTI-VEHICLE TRANSMISSION FLUID

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TYPICAL CHARACTERISTICS

SYN-TS® LV	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.846
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	29
@ 100°C	ASTM D445	cSt	6.0
Viscosity Index	ASTM D2270	-	158
Brookfield Viscosity @ -40°C	ASTM D2983	mPa.s	10,600
Pour Point	ASTM D97	°C	-45
Flash Point (COC)	ASTM D92	°C	200

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

300023

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398