

# SYN-X 3000 10W-40

**SEMI SYNTHETIC, SN/CF, A3/B4, PREMIUM PASSENGER CAR MOTOR OIL**

## DESCRIPTION

Syn-X 3000 10W-40 is a premium blend semi-synthetic motor oil suitable for most Australian, US, European and Asian engines calling for a SAE 10W-40 or 15W-40 engine oil with API SN/CF or earlier performance levels. It is formulated using a combination of synthetic and premium hydrotreated mineral base oils and a modern additive package meeting the API SN/CF and ACEA A3/B4 performance requirements. Syn-X 3000 10W-40 offers superior levels of protection against engine wear, excellent engine cleanliness by controlling deposit and sludge formation, superior cold flow performance and high operating temperature oxidation control. May also be used in motorcycles with wet clutch operation. Syn-X 3000 10W-40 is a highly versatile engine oil that can be used in a wide range of operating conditions including severe, modern stop-start driving conditions.

**Recommended for:** Cars, vans, utility vehicles and 4WD engines whether naturally aspirated or turbo charged running on Unleaded Petrols, LPG or diesel fuel where API SN/CF, ACEA A3/B4 specifications are called for.

## SUMMARY OF BENEFITS

- Excellent flow and pumpability on cold start
- Meeting the latest global API technology
- Semi synthetic providing fuel saving capability
- Semi synthetic providing reduced oxidation and viscosity breakdown
- Superior sludge and varnish control for a cleaner engine
- Reduced oil consumption due to improved volatility control
- Greatly reduced engine wear giving extended engine life
- High shear strength
- Excellent volatility

## SPECIFICATIONS

Syn-X 3000 10W-40 meets the following international performance specifications:

- SAE 10W-40
- API SN/CF
- ACEA A3/B3/B4
- MB 229.3
- VW 502.00/505.00
- Renault RN0700/RN0710
- CHRYSLER MS 6395
- GM 6094M
- JASO MA

## STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

**Head Office:** 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

**Phone:** 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

**ACN:** 087 558 398

# SYN-X 3000 10W-40

SEMI SYNTHETIC, SN/CF, A3/B4, PREMIUM PASSENGER CAR MOTOR OIL

## TYPICAL CHARACTERISTICS

SYN-X 3000 10W-40	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.887
Kinematic Viscosity @ 40°C	ASTM D445	cSt	105
@ 100°C	ASTM D445	cSt	15.0
Viscosity Index	ASTM D2270	-	136
Pour Point	ASTM D97	°C	-34
Flash Point (COC)	ASTM D92	°C	>224
Total Base Number	ASTM D2896	mgKOH/g	9.02

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

## AVAILABLE PACK SIZES

205lt - 30037, 20lt - 32037, 6lt - 30637, 5lt - 30537, 1lt - 30137