



SYN-X 4000 5W-30

LOW VISCOSITY, FULL SYNTHETIC ENGINE OIL MEETING GM DEXOS 1 GEN 2, API SP, ILSAC GF-6A

DESCRIPTION

Syn-X 4000 is a high performance engine lubricant meeting the demanding GM Dexos 1 Generation 2 (D1G2) engine oil specification. It has been designed to provide excellent fuel efficiency whilst offering exceptional engine protection in the harshest conditions including cold start and constant stop-start driving. Formulated using the latest API additive technology Syn-X 4000 has been developed to be used in all modern General Motors petrol engines, including turbo charged gasoline direct injection engines where the advanced chemistry protects against LSPI and timing chain wear.

Syn-X 4000 is suitable for most modern passenger cars calling for a lubricant meeting API SP, ILSAC GF-6A, GM Dexos 1 Generation 2 or earlier specifications in a resource conserving SAE 5W-30 viscosity grade.

SUMMARY OF BENEFITS

- Full Synthetic formulation
- Protects against LSPI (low speed pre-ignition)
- Enhanced timing chain wear protection
- Resource Conserving formulation exceeding ILSAC GF-6A
- Super extended drain intervals surpassing any mineral based lubricant
- Excellent soot and sludge control resulting in cleaner engines
- Outstanding low temperature viscometrics for reduced wear at start up

SPECIFICATIONS

Syn-X 4000 5W-30 meets the following international performance specifications:

- SAE Viscosity 5W-30
- GM Dexos 1 Generation 2
- API SP
- ILSAC GF-6A

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398

SYN-X 4000 5W-30

LOW VISCOSITY, FULL SYNTHETIC ENGINE OIL MEETING GM DEXOS 1 GEN 2, API SP, ILSAC GF-6A

TYPICAL CHARACTERISTICS

SYN-X 4000 5W-30	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.852
Kinematic Viscosity @ 40°C	ASTM D445	cSt	64
@ 100°C	ASTM D445	cSt	10.6
Viscosity Index	ASTM D2270	-	>156
Pour Point	ASTM D97	°C	-36
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	8.6
Sulphated Ash	ASTM D874	% mass	<0.9

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 60001, 20lt - 62001, 5lt - 60501